

FIG. 1
(PRIOR ART)




FIG. 2
(PRIOR ART)




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5




FIG. 6

FIG. 6 is a schematic diagram of a mechanical assembly in a cross-sectional view. The assembly includes a main body 1 with a longitudinal slot 10. A component 2 is positioned within the slot, featuring a series of teeth or projections 14. A curved arrow indicates the rotation of component 2 around a pivot point 4. Various sub-components are labeled with reference numerals: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100. A dashed line 3 indicates a specific feature or boundary.